



VPSII

PRODUCT INFORMATION

- ✓ OIML-R76 and EC Class III Type Approved
- ✓ All Stainless Steel Housing, Platform and Pillar Sealed Indicator
- ✓ Wash Down Design According to IP65
- ✓ Flexible Platform Collocation
- ✓ Two Platform Structures Available for Different Operating Environment: Erosion Proof Version (Stainless Steel Load Cell and Load Receiving Structure)
- ✓ 5 1/2 x 25mm Wide Angle LCD (Backlight)
- ✓ User Programmable Capacity and Division
- ✓ Power ON Zero Tracking, Re-zero, Auto Calibration, Auto Power Saving, Digital Motion Filtering Device, Auto Tare, Accumulation Memory and Dual Interval Selection Functions
- ✓ Complete with Low Battery and Charging Status Indicator
- ✓ Adjustable Feet, Rechargeable Battery, Bubble Level, Power Adaptor and Indicator Dust Cover Included
- ✓ Pan size: 280 x 330 mm
- ✓ Options available: RS-232 Interface



Model	Capacity	Readability
VPS II-6	3 / 6 kg	1 / 2 g
VFS II-15	6 / 15 kg	2 / 5 g
VFS II-30	15 / 30 kg	5 / 10 g

